






Genuine Parts Service

STU Single Universal Twister

Highly flexible single twister with individual positions twisting Carbon yarns, advanced composite fibers, PVC monofilament

MAIN BENEFITS

- Very broad spectrum of applications in single twisting
- Smart modular design mixing frames (different gauges, air pressurisation/suction systems) and processes (single twisting, multi ply assembling) on the same machine
- Self sufficient motorspindle enabling individual settings for each position
- Individual single twist position technology driven by separate spindle, capstan, yarn guide and winding systems
- Innovative adjustable electronic traverse motion for flexible wound package constructions
- Advanced web based machine control via your PC
- Set, Save, Share Settings: a unique unlimited database «S⁴» concept of recipes at your fingertips!



45500

GENERAL FEATURES

Maximum spindle number 120/96
Spindle gauge (mm) 730/900
Maximum section 20/24
Section length (mm) 2190/1800
Maximum length (m) 45.5
Machine width (mm) 1900
Delivery speed (m/min) 200
Twist (tpm) 7 to 500

SUPPLY

Type Cardboard cylindrical,
milk bottle, flanged bobbin
Yarn count (tex) 100 to 4500
Maximum bobbin diam. (mm) 300
Maximum weight (Kg) 10

SPINDLE

Drive Single twist motorspindle
Yarn break sensor Electronic
Maximum speed (rpm) 8000

TAKE UP

Maximum diameter (mm) 400

Package traverse 10in/12in on cardboard cylindrical tube

Maximum weight (Kg) 10

Cradle Pneumatical

OPTIONS

Multi ply assembling. Electronic traverse motion system. Electronic overfeed. Noise reduction. Combined gauges. Combined air pressurisation/suction frames. Load cell

Contact us



FRANCE







www.e-tex.fr



